

MAXICHARGER ACCOMMERCIAL

11.5KW

Part Number: MCC50AHI



TECHNICAL SPECIFICATIONS

POWER

INPUT/OUTPUT POWER RATING & CURRENT INPUT/OUTPUT VOLTAGE	12kW (240V AC*50A) 208V±15%; 240V±15%, 60Hz
NETWORK TYPE	L1/N+PE, L1/L2/PE
INPUT CORD	Hardwired
CONNECTOR TYPE	SAE J1772, 25ft (7.5m)
GROUND FAULT DETECTION	20mA CCID
PROTECTION	Overcurrent, Overvoltage, Undervoltage, Integrated Surge Protection Full Scale
POWER MEASUREMENT ACCURACY	

OPERATIONAL RATINGS

ENCLOSURE RATING	NEMA 4
OPERATING TEMPERATURE RANGE	-40°F ~+131°F (-40°C ~+55°C)
STORAGE TEMPERATURE RANGE	-40°F ~+185°F (-40°C ~+85 °C) Wall Or
MOUNTING	Floor Using A Pedestal
DIMENSIONS (H*W*D)	13.23"x7.36"x3.35" (336×187×85mm)

USER INTERFACE

STATUS INDICATION	LED/APP/Touch Screen (5 Inch LCD, 800*480)
USER INTERFACE	EV-olution Charge APP; EV-olution Charge Cloud
CONNECTIVITY	Bluetooth, Wi-Fi, Ethernet, 4G, CAN, RS485 OCPP
COMMUNICATION PROTOCOLS	1.6J (Can Be Upgraded To OCPP 2.0.1 Later) APP,
USER AUTHENTICATION	RFID Card
CARD READER	ISO 15693, ISO 14443, NFC
SOFTWARE UPDATE	OTA

CERTIFICATION & STANDARDS

SAFETY & COMPLIANCE	UL 2231-1, UL 2231-2, UL2594, NEC Article 625, CSA C22.2, UL 916 FCC 15 Class B
EMC COMPLIANCE	Energy Star, OpenADR 2.0b
CERTIFICATION	36 Months, Warranty Extension Available
WARRANTY	